



NORGLASS PAINTS

and Specialty Finishes

Australian Made / Australian Owned

Date of Issue: July 2014
Pages: 1 of 3

MATERIAL SAFETY DATA SHEET

PRODUCT: WEATHERFAST PREMIUM SATIN ENAMEL

IDENTIFICATION

CLASSIFICATION	:	HAZARDOUS. According to criteria of Worksafe Australia.
Product Name	:	Weatherfast Premium Satin White
Other Names	:	Enamel Paint - Air Drying
Manufacture's Product Code	:	8400
UN Number	:	1263
Correct Shipping Name	:	Paint, flammable liquid
Dangerous Goods Class & Subsidiary Risk	:	3.2
Hazchem Code	:	3[Y] PG III
Poison Schedule Number	:	Not available
Use	:	White satin finish water resistant paint for interior and exterior use. Applied by brush, roller or spray.

PHYSICAL DESCRIPTION/PROPERTIES

Appearance	:	Coloured viscous liquid with low solvent odour.
Boiling Point °C	:	150 - for solvent
Melting Point °C	:	Not measured
Vapour Pressure 25 °C	:	Not available
Flash Point °C	:	32
Volatile Component	:	20-25%
Specific Gravity	:	0.930 - 1.180
Flammability Limits	:	not measured
Solubility in Water	:	Insoluble

INGREDIENTS

Chemical Entity	CAS Number	Proportions w/w
Urethane Alky Resin	Proprietary	50-69%
White Spirit	64742-88-7	10-15%
Pigments various Additives	Proprietary “	5-20% up to 100

HEALTH HAZARD INFORMATION

Health Effect	:	No LD50 data or toxicological data available for this product. Exposure to inhalation or ingestion can be harmful as the product contains lead driers 1.8/L. Eye irritant and defatting of skin.
Acute	:	
Swallowed	:	Harmful if swallowed. May cause irritation of mouth, throat and digestive system. Cause damage to mucous membrane.
Eye	:	Severe eye irritant.
Skin	:	Irritant and defatting of skin.
Inhaled	:	Concentrated solvent vapour can cause irritation to respiratory system.
Chronic	:	Prolonged and repeated exposure may develop allergic reactions. Inhalation of concentrated vapour can cause nausea and headaches.

FIRST AID

Swallowed	:	Get medical attention immediately. Do not induce vomiting. If the victim is conscious give water or milk to drink to dilute the effect. If unconscious and vomiting, take precautions to prevent vomit from entering lungs. Contact Poisons Information Centre on 131 126.
Eye	:	Flush with water for at least 20 minutes with eye lids open also get medical attention.
Skin	:	Mild skin irritant. Repeated or prolonged skin contact may develop skin sensitisation or dermatitis.
Inhaled	:	Remove victim to fresh air. If breathing is difficult administer artificial respiration or give oxygen where necessary. Get medical advice if effect persists.
First Aid Facilities	:	General first aid facilities should be available where product is used. Barrier Cream, Cleaning Cream, showers and eye wash facilities a must.
Advice to Doctor	:	Treat symptomatically. No specific antidote

PRECAUTION FOR USE

Exposure standards	:	No specific exposure standard. Avoid excessive exposure by use of proper ventilation and or personal protection. Follow good workplace practice. Handle with care. Avoid inhalation, ingestion, eye and skin contact at all times. Do not smoke, chew or eat while using the product.
--------------------	---	---

Engineering Controls	:	Use only in well ventilated areas. Introduce local exhaust ventilation if necessary. Strictly follow State or Territory regulations.
Personal Protection	:	Wear overalls, use Barrier Cream. Avoid eye and skin contact be wearing safety goggles and neoprene rubber gloves. Avoid breathing vapour of dust by wearing organic vapour respirators.
Flammability	:	Flammable liquid, use in well ventilated areas. Do not smoke while handling this product. Eliminate all sources of ignition.
Environment	:	

SAFE HANDLING INFORMATION

Storage and Transport	:	Product should be handled as flammable material. Dangerous Goods Class 3. Must be stored and transported in accordance with Federal, State or Territory Dangerous Goods regulations Partly used containers must be properly sealed. Keep out of reach of children.
Spills and disposal	:	Extinguish all sources of ignition. Wear protective clothing. Spilt material should be absorbed into dry inert material such as sand, earth or sawdust and disposed by incineration by approved agent or local regulations. Adequate steps should be taken to prevent spillage reaching waterways and drains.
Fire/Explosion Hazard	:	Flammable liquid and vapour, can explode if ignited. Extinguishing media carbon dioxide foam or dry chemicals.

Other Handling Information:

Contact Point: Mr Les Baker
NORGLASS LABORATORIES PTY. LIMITED

The information contained in this material safety sheet is based on tests carried out by our research centres and data selected from literature, but shall in no event be held to constitute or imply any warranty or understanding. No liability whatsoever can be accepted with regard to handling, processing or use of the product or products concerned, which in all cases be employed with due regard to all relevant regulations and/or legislation in the country or countries concerned.

NORGLASS LABORATORIES PTY LTD ABN: 92 001 807 245 www.norglass.com.au

Factory: 59 Moxon Rd, Punchbowl NSW 2196 Ph: 02 9708 2200 Fax: 02 9796 3069 Email: norglass@bigpond.net.au
Postal: P.O Box 312, Neutral Bay NSW 2089 Accts Ph: 02 9908 1239 Fax: 02 9908 1783 Accts: amsd@bigpond.net.au