

WAX AND GREASE REMOVER

DESCRIPTION: Wax and Grease Remover is a cleaning solvent solution that effectively removes surface contaminants such as grease, silicone polishes, oils, road scum and the like prior to painting.

PROPERTIES (at 20degreesC)

APPEARANCE: Clear liquid with mild odour.

TOXICITY: Contains hydrocarbons. Refer to Safety Directions and First Aid instructions on the label.

SHELF LIFE: Indefinite.

WEIGHT/LITRE: 0.75-0.85

FLASH POINT: <0

UN NUMBER: 1263 PAINT

APPLICATION:

Wet a clean soft cloth with Wax and Grease Remover and thoroughly Clean the surface to be painted using a circular rubbing motion. Using a second clean soft cloth wipe off the solution. It is important to use separate cloths for wiping on and wiping off and that the cloths are replaced periodically with clean ones.

Do not attempt to clean too large a surface area at a time because if allowed to evaporate, the dissolved oil and grease etc. will be re-deposited on the surface.

For heavily soiled and contaminated surfaces, repeat the process.

Wax and Grease Remover can also be soaked on a nylon scouring pad and used to remove oxidation from aluminium surfaces.

Wax and Grease Remover will not leave any solid residue on the surface. It is a mild solvent blend that will not soften or damage acrylic lacquers, enamels, polyurethane, 2K Acrylic urethane, epoxies, gelcoats, fibreglass etc.

PRECAUTIONS:

HIGHLY FLAMMABLE
AVOID BREATHING VAPOUR
AVOID CONTACT WITH SKIN
AVOID CONTACT WITH EYES