

SAFETY DATA SHEET

Section 1. Identification of the material and the supplier

Product: **Northane Brushing Thinner**
 Item Code: 3033
 UN No: 1993
 Product Use: Solvent/Thinner
 Restriction of Use: Refer to Section 15

Australian Manufacturer: **Norglass Paints**
 Address: 59 Moxon Road
 Punchbowl NSW 2196
 Australia
 Telephone: +61 2 9708 2200
 Email: info@norglass.com.au

New Zealand Supplier: xxx
 Address: xxx
 Telephone: 0508 724687

Emergency Numbers:
Australia: 13 1126 (Poisons Information Centre)
New Zealand: 0800 764 766 (National Poison Centre)

Date of SDS Preparation: 7 November 2016 v2

Section 2. Hazards Identification

This substance is hazardous according to:
New Zealand - The HSNO (Minimum Degrees of Hazard) Regulations 2001
Australia – Approved Criteria for Classifying Hazardous Substances
[NOHSC:1008(2004)]

New Zealand:

EPA Approval No: Surface Coatings and Colourants (Flammable) – HSR002662

Pictograms



Flammable



Chronic

Signal Word: DANGER

HSNO Classification	Hazard Code	Hazard Statement	GHS Category
3.1C	H226	Flammable liquid and vapour.	Category 3
6.1E (asp)	H304	May be fatal if swallowed and enters airways.	Category 1

6.8A	H360	May damage fertility or the unborn child.	Category 1A
------	------	---	-------------

Prevention Code	Prevention Statement
P102	Keep out of reach of children.
P103	Read label before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, sparks, open flames or hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P280	Wear protective clothing.
P281	Use personal protective equipment as required.

Response Code	Response Statement
P101	If medical advice is needed, have product container or label at hand.
P331	Do NOT induce vomiting.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303 + P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P370 + P378	In case of fire: Use carbon dioxide, foam or dry chemicals for extinction.

Storage Code	Storage Statement
P405	Store locked up.
P403 + P235	Store in a well-ventilated place. Keep cool.

Disposal Code	Disposal Statement
P501	Dispose of according to Local Regulations or Authorities

Section 3. Composition / Information on Ingredients

Ingredients	Wt%	CAS NUMBER.
Propylene Glycol 2, Methylene Acetate	98	70657-70-4

Section 4. First Aid Measures

Routes of Exposure:

If in Eyes	Rinse cautiously with water for several minutes. If eye irritation persists: Get medical advice.
If on Skin	Wash with plenty of soap and water. If skin irritation or rash occurs: get medical advice/attention.
If Swallowed	Rinse mouth. DO NOT induce vomiting. If the victim is conscious give water or milk to drink to dilute the effect. If vomiting occurs, place victim face downwards, with the head turned to the side and lower than the hips to prevent vomit entering the lungs. Seek immediate medical attention.
If Inhaled	Remove person to fresh air. Remove contaminated clothing and loosen remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Get medical advice if breathing becomes difficult.

Section 5. Fire Fighting Measures

Hazard Type	Flammable liquid. May form flammable vapour mixtures with air.
Hazards from combustion products	On burning will emit toxic fumes.
Suitable Extinguishing media	Extinguishing media: water fog, carbon dioxide, foam or dry chemicals.
Precautions for firefighters and special protective clothing	Wear full body protection and self-contained breathing apparatus.
HAZCHEM CODE	3Y

Section 6. Accidental Release Measures

Wear protective equipment as detailed in Section 8. Clear area of any unprotected personnel.

Extinguish all sources of ignition. Spilt material should be absorbed into dry inert material such as sand, earth or sawdust and disposed by incineration by approved agent or local regulations. Adequate steps should be taken to prevent spillage reaching waterways and drains.

Section 7. Handling and Storage

Precautions for Handling:

- Read label before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat, sparks, open flames or hot surfaces. No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use only outdoors or in a well-ventilated area.
- Use explosion-proof electrical/ventilating/lighting.
- Use only non-sparking tools.
- Wear protective clothing and equipment.

Precautions for Storage:

- Store away from incompatible materials listed in Section 10.
- Store locked up, in a well-ventilated place. Keep cool.
- Product should be stored in properly sealed containers, if at all, not used in one application.
- Keep out of reach of children.

Section 8 Exposure Controls / Personal Protection

WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

Substance	TWA		STEL	
	ppm	mg/m ³	ppm	mg/m ³

No substances have exposure limits.

Workplace Exposure Standard – Time Weighted Average (WES-TWA). *The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure.* Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). *The 15-minute average exposure standard.* Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply.

Engineering Controls

Use only in well-ventilated area or with local exhaust ventilation or while wearing organic vapour respirators, or air supplied mask.

Personal Protection

Eyes	Wear safety goggles with side shields.
Hands and Skin	Wear impervious gloves. Wear overalls.
Respiratory	Use adequate ventilation if inhalation risk exists wear organic vapour respirators.

Section 9 Physical and Chemical Properties

Appearance	Colourless liquid
Odour	Mild odour
Odour Threshold	Not applicable
pH	Not applicable
Boiling Point	146°C
Melting Point	Not applicable
Freezing Point	Not applicable
Flash Point	50°C(PMC)
Flammability	Not applicable
Upper and Lower Exposure Limits	Not applicable
Volatile Component	100%
Vapour Pressure 20°C	0.5kPa
Specific Gravity	0.97
Solubilities	Miscible
Partition Coefficient:	Not applicable
Auto-ignition Temperature	Not applicable
Decomposition Temperature	Not applicable
Kinematic Viscosity	Not applicable
Particle Characteristics	Not applicable

Section 10. Stability and Reactivity

Stability of Substance	This product is stable under normal conditions.
Conditions to Avoid	Sources of ignition. Heat.
Incompatible Materials	Not to be loaded with explosives, flammable gases, poisonous gases, spontaneously combustible substances, oxidising agent, organic peroxides.
Hazardous Decomposition Products	On burning will emit toxic fumes.

Section 11 Toxicological Information

Acute Effects:

Swallowed	Not applicable.
Dermal	Not applicable.
Inhalation	Not applicable.
Eye	Not applicable.
Skin	Not applicable.

Chronic Effects:

Carcinogenicity	Not applicable.
Reproductive Toxicity	May damage fertility or the unborn child.
Germ Cell	Not applicable.

Mutagenicity	
Aspiration	May be fatal if swallowed and enters airways.
STOT/SE	Not applicable.
STOT/RE	Not applicable.

Section 12. Ecotoxicological Information

This product is not hazardous to the environment.

Persistence and degradability	No data available
Bioaccumulation	No data available
Mobility in Soil	No data available
Other adverse effects	No data available

Section 13. Disposal Considerations

Disposal Method: Place recovered product into an appropriate waste container for disposal through appropriate waste company or specialized landfill in accordance with local regulations. Ensure container is sealed and isolated away from ignition sources.

Precautions: Ensure waste container containing recovered product is labelled "Hazardous Waste – Flammable". If triple rinsing container, add rinsate to waste container for disposal.

Disposal methods to avoid: None known.

Section 14 Transport Information

This product is classified as a Dangerous Good for transport in NZ ; NZS 5433:2012 and Australian Dangerous Goods Code ADG7 and NOHSC:1008(2004)

Road and Rail Transport

UN No: 1993
 Class-primary 3
 Packing Group III
 Proper Shipping Name: FLAMMABLE LIQUID, N.O.S.

Air Transport

UN No: 1993
 Class-primary 3
 Packing Group III
 Proper Shipping Name: FLAMMABLE LIQUID, N.O.S.

Marine Transport

UN No: 1993
 Class-primary 3
 Packing Group III
 Proper Shipping Name: FLAMMABLE LIQUID, N.O.S.

Section 15 Regulatory Information

This substance is hazardous according to:
New Zealand - The HSNO (Minimum Degrees of Hazard) Regulations 2001
Australia – Approved Criteria for Classifying Hazardous Substances
[NOHSC:1008(2004)]

Poison Schedule: Not Scheduled

New Zealand:

EPA Approval Code: Surface Coatings and Colourants (Flammable) – HSR002662

HSNO Classification: 3.1C, 6.1E(asp), 6.8A

HSNO Controls:

Trigger quantities for this substance:

	Trigger Quantity
Approved Handler	Not required
Location Certificate	500L (>5L), 1500L(<5L), 250L open
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	1 000L
Emergency Response Plan	10 000L
Stationery containment	10 000L
Restriction of Use	None

Section 16 Other Information**Glossary**

EC50	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms.
LC50	Lethal concentration that will kill 50% of the test organisms inhaling or ingesting it.
LD50	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.
TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit

1. HSNO Approved Code of Practice: Preparation of Safety Data Sheets, September 2006.
2. Australia – Approved Criteria for Classifying Hazardous Substances -[NOHSC:1008(2004)]
3. Safework Australia: Preparation of SDS sheets for hazardous chemicals (Code of Practice).

Disclaimer

This document has been issued by TCC (NZ) Ltd and serves as their Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the Australian manufacturer, if further information is required.

Issue Date: 7 November 2016

Review Date: 7 November 2021