



MATERIAL SAFETY DATA SHEET

PRODUCT: WEATHERFAST DECK PAINT

IDENTIFICATION

CLASSIFICATION	:	HAZARDOUS. According to criteria of Worksafe Australia.
Product Name	:	DECK PAINT - VARIOUS COLOURS
Other Names	:	SLIP RESISTANT DECK PAINT
Manufacturers Product Code	:	8100
UN Number	:	1263
Correct Shipping Name	:	Paint - Flammable Liquid
Dangerous Goods Class & Subsidiary Risk	:	3.2
Hazchem Code	:	3[Y] PG III
Poison Schedule Number	:	Not Available
Use	:	Paint on Concrete, Fibrous Sheeting & Timber Air Dry Enamel applied by brush roller or spray, in accordance with Product Data Sheet.

PHYSICAL DESCRIPTION/PROPERTIES

Appearance	:	White or coloured viscous liquid with low solvent odour.
Boiling Point C°	:	150 deg. C - solvent
Vapour Pressure 25 C°	:	Not measured.
Specific Gravity	:	1.120 - 1.220
Flashpoint C°	:	32
Flammability limits	:	Not measured
Solubility in water	:	Insoluble

INGREDIENTS

Chemical Entity	CAS Number	Proportions
Urethane Alkyd Resin	Proprietary	40-45% wt
Pigments	Various	30-35% wt
White Spirits	64742-88-7	12-15% wt
Additives	Proprietary	< than 5%

HEALTH HAZARD INFORMATION

Health Effect	:	No adverse health effect expected if the product is handled carefully and in accordance with label instructions and proper safety measures. Avoid prolonged exposure to solvent vapours.
Acute	:	
Swallowed	:	Harmful if swallowed. May cause irritation of mouth, throat and digestive system, resulting in nausea and vomiting.
Eye	:	Mild eye irritation.
Skin	:	Irritant and defatting of skin.
Inhaled	:	Concentrated solvent vapours can cause irritation of respiratory system.
Chronic	:	Not known.

FIRST AID

Swallowed	:	Seek IMMEDIATE medical attention. DO NOT induce vomiting. If the victim is conscious, give water to drink to dilute the effect. If vomiting, take precaution to prevent vomit from entering lungs. DO NOT give a drink to an unconscious person. Contact Poisons Information Centre on 131 126.
Eye	:	Flush eye with water for at least 20 minutes. If effect persists, seek medical attention.
Skin	:	Remove contaminated clothes and shoes. Wash skin with cleaning cream and then with soap and water. DO NOT USE SOLVENTS.
Inhaled	:	Remove to fresh air. If difficulty in breathing, administer artificial respiration. Seek medical assistance if effect persists.
First Aid facilities	:	General first aid facilities such as cleansing cream, barrier cream, eye lotion, eye wash fountains and showers should be available at hand.
Advice to Doctor	:	Treat symptomatically - No antidote.

PRECAUTION FOR USE

Exposure standards	:	No specific exposure standards. Avoid excessive exposure by use of proper ventilation and personal protection. Handle with care. Follow sound workplace practice. Avoid inhalation ingestion, eye and skin contact. Do not smoke, eat or drink while using the product.
--------------------	---	---

Engineering controls	:	Use only in well ventilated areas. Strictly follow, Federal, State and Territory Regulations. Local exhaust ventilation is usually required. Provide explosion proof ventilation system. Respiratory protection required if air contamination level exceeds the exposure limit.
Personal Protection	:	Wear overall, use barrier cream. Avoid eye and skin contact by wearing safety goggles and neoprene gloves. Avoid breathing vapours and dust by wearing organic vapour respirators. (approved respirators).
Flammability	:	Flammable liquid, Class 3.2. Keep away from heat, sparks and naked flames. Do not smoke. Use only in well ventilated areas.

SAFE HANDLING INFORMATION

Storage and Transport	:	<p>Store in a cool place, well ventilated area, away from heat, naked flames and sparks. Keep containers closed at all times. Do not obliterate label instructions on partly used containers.</p> <p>Store away from food, food stuffs, clothing and drinks. Take precaution against static electricity discharges. Keep out of reach of children. Class 3 label according to transport of “dangerous goods”.</p>
Spills and disposal	:	Extinguish all sources of ignition. Wear suitable protective clothing. Spilt material should be absorbed onto dry sand, sawdust or earth and disposed of according to local regulation either by incineration or buried in approved landfill. Do not contaminate streams, driveways and waterways.
Fire/Explosion Hazard	:	<p>To extinguish fire, use foam, carbon dioxide or dry chemicals. Wear full body protective clothing and self contained breathing apparatus for major fires. Water spray may be used to keep fire from exposed containers cool. Hazardous polymerisation will occur. Flammable liquid and vapours can explode if ignited.</p> <p>Burning may produce carbon monoxide and carbon dioxide.</p>
Contact Point:		<p>Mr Brett Mould NORGLASS LABORATORIES PTY. LIMITED</p>

The information contained in this material safety sheet is based on tests carried out by our research centres and data selected from literature, but shall in no event be held to constitute or imply any warranty or understanding. No liability whatsoever can be accepted with regard to handling, processing or use of the product or products concerned, which in all cases be employed with due regard to all relevant regulations and/or legislation in the country or countries concerned.

NORGLASS LABORATORIES PTY LTD ABN: 92 001 807 245 www.norglass.com.au

Factory: 59 Moxon Rd, Punchbowl NSW 2196 Ph: 02 9708 2200 Fax: 02 9796 3069 Email: norglass@bigpond.net.au
Postal: P.O Box 312, Neutral Bay NSW 2089 Accts Ph: 02 9908 1239 Fax: 02 9908 1783 Accts: amsd@bigpond.net.au