

SAFETY DATA SHEET

Section 1.	Identification of the material and the supplier
------------	---

Product:	Norshield Anit-Corrosive Primer Base
Item Code:	4070
UN No:	1263
Product Use:	As a primer for ferrous and non-ferrous metals. Applied by brush, roller or spray.
Restriction of Use:	Refer to Section 15
Australian Manufacturer:	Norglass Paints
Address:	59 Moxon Road Punchbowl NSW 2196 Australia
Telephone:	+61 2 9708 2200
Email:	info@norglass.com.au
New Zealand Supplier:	xxx
Address:	xxx
	xxx
Telephone:	0508 724687
Emergency Numbers:	
Australia:	13 1126 (Poisons Information Centre)
New Zealand:	0800 764 766 (National Poison Centre)
Date of SDS Preparation:	7 November 2016 v2

Section 2.	Hazards Identification
------------	------------------------

This substance is hazardous according to:
New Zealand - The HSNO (Minimum Degrees of Hazard) Regulations 2001
Australia – Approved Criteria for Classifying Hazardous Substances
[NOHSC:1008(2004)]

New Zealand:
EPA Approval No:
Surface Coatings and Colourants (Flammable, Toxic [6.7]) – HSR002669

Pictograms



Signal Word: **DANGER**

HSNO Classification	Hazard Code	Hazard Statement	GHS Category
3.1C	H226	Flammable liquid and vapour.	Category 3

6.1E (asp)	H304	May be fatal if swallowed and enters airways.	Category 1
6.3A	H315	Causes skin irritation.	Category 2
6.5B	H317	May cause an allergic skin reaction.	Category 1
6.7B	H351	Suspected of causing cancer.	Category 2
6.8B	H361	Suspected of damaging fertility or the unborn child.	Category 2
6.9B	H373	May cause damage to organs through prolonged or repeated exposure.	Category 2
8.3A	H318	Causes serious eye damage.	Category 1
9.1D(NZ only)	H401	Toxic to aquatic life.	Category 4
9.3C(NZ only)	H433	Harmful to terrestrial vertebrates.	

Prevention Code	Prevention Statement
P102	Keep out of reach of children.
P103	Read label before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, sparks, open flames or hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust, fume, gas, mist or vapours.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective clothing.
P281	Use personal protective equipment as required.

Response Code	Response Statement
P101	If medical advice is needed, have product container or label at hand.
P310	Immediately call a POISON CENTER or doctor/physician.
P331	Do NOT induce vomiting.
P362	Take off contaminated clothing and wash before re-use.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303 + P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305 + P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P370 + P378	In case of fire: Use carbon dioxide, foam or dry chemicals for extinction.

Storage Code	Storage Statement
P405	Store locked up.
P403 + P235	Store in a well-ventilated place. Keep cool.

Disposal Code	Disposal Statement
P501	Dispose of according to Local Regulations or Authorities

Section 3. Composition / Information on Ingredients

Ingredients	Wt%	CAS NUMBER.
Pigments and Extenders	Proprietary	58%
Bisphenol A Epoxy Resin Solid	25068 - 38 - 6	14%
Xylene	1330 - 20 - 7	15.7%
Glycol ether	107 - 98 - 2	5.9%

Butanol	78 - 83 - 1	5.2%
Butylated Urea Formaldehyde Resin solid	68002 - 18 - 6	1.2%

Section 4. First Aid Measures

Routes of Exposure:

If in Eyes	Rinse cautiously with water for several minutes. Get immediate medical attention.
If on Skin	Wash with plenty of soap and water. Take off contaminated clothing and wash before re-use. If skin irritation or rash occurs: get medical advice/attention.
If Swallowed	Rinse mouth. DO NOT induce vomiting. If the victim is conscious give water or milk to drink to dilute the effect. If vomiting occurs, place victim face downwards, with the head turned to the side and lower than the hips to prevent vomit entering the lungs. Seek immediate medical attention.
If Inhaled	Remove person to fresh air. Remove contaminated clothing and loosen remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Get medical advice if breathing becomes difficult.

Section 5. Fire Fighting Measures

Hazard Type	Flammable liquid vapours can explode in air if ignited.
Hazards from combustion products	Toxic gases and vapours can be formed on burning.
Suitable Extinguishing media	Extinguishing media carbon dioxide, foam or dry chemicals.
Precautions for firefighters and special protective clothing	Wear full body protection and self-contained breathing apparatus. Wear self-contained breathing apparatus and full protective clothing. Cured material made using this product if machined or sanded, a dust explosion hazard may be created. Hence, all dust generated should be removed as quickly as possible preferably by vacuum cleaner.
HAZCHEM CODE	3Y

Section 6. Accidental Release Measures

Wear protective equipment as detailed in Section 8. Clear area of any unprotected personnel.

Extinguish all sources of ignition. Spilt material should be absorbed into dry inert material such as sand, earth or sawdust and disposed by incineration by approved agent or local regulations. Adequate steps should be taken to prevent spillage reaching waterways and drains.

Section 7. Handling and Storage

Precautions for Handling:

- Read label before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat, sparks, open flames or hot surfaces. No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use only outdoors or in a well-ventilated area.
- Use explosion-proof electrical/ventilating/lighting.

- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Do not breathe dust, fume, gas, mist or vapours.
- Wash hands thoroughly after handling.
- Contaminated work clothing should not be allowed out of the workplace.
- Wear protective clothing and equipment.

Precautions for Storage:

- Store away from incompatible materials listed in Section 10.
- Store locked up, in a well-ventilated place. Keep cool.
- Product should be stored in properly sealed containers, if at all, not used in one application.
- Keep out of reach of children.

Section 8 Exposure Controls / Personal Protection

WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

Substance	TWA		STEL	
	ppm	mg/m ³	ppm	mg/m ³
Xylene	50	217	-	-

Workplace Exposure Standard – Time Weighted Average (WES-TWA). *The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure.* Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). *The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply.*

Engineering Controls

Use only in well ventilated areas.

Personal Protection

Eyes	Wear safety goggles with side shields.
Hands and Skin	Wear neoprene rubber gloves. Wear overalls and use barrier cream.
Respiratory	Avoid breathing solvent vapours by wearing organic vapour respirators. Do not use disposable dust masks.

Section 9 Physical and Chemical Properties

Appearance	Red pigmented viscous liquid
Odour	Solvent odour
Odour Threshold	Not applicable
pH	Not applicable
Boiling Point	137-143°C for solvent
Melting Point	Not applicable
Freezing Point	Not applicable
Flash Point	38°C(solvent)
Flammability	Not applicable
Upper and Lower Exposure Limits	Not applicable
Volatile Component	18.5
Vapour Pressure 25°C	Not applicable
Specific Gravity	1.745
Solubilities	Insoluble
Partition Coefficient:	Not applicable
Auto-ignition Temperature	Not applicable

Decomposition Temperature	Not applicable
Kinematic Viscosity	Not applicable
Particle Characteristics	Not applicable

Section 10. Stability and Reactivity

Stability of Substance	This product is stable under normal conditions.
Conditions to Avoid	Sources of ignition. Heat.
Incompatible Materials	None known.
Hazardous Decomposition Products	None known.

Section 11 Toxicological Information

Acute Effects:

Swallowed	Not applicable.
Dermal	Not applicable.
Inhalation	Not applicable.
Eye	Causes severe eye damage.
Skin	Causes skin irritation. May cause an allergic skin reaction.

Chronic Effects:

Carcinogenicity	Suspected of causing cancer.
Reproductive Toxicity	Suspected of damaging fertility or the unborn child.
Germ Cell Mutagenicity	Not applicable.
Aspiration	May be fatal if swallowed and enters airways.
STOT/SE	Not applicable.
STOT/RE	Causes damage to organs through prolonged or repeated exposure.

Section 12. Ecotoxicological Information

New Zealand:

HSNO Classes: 9.1D = Toxic to aquatic life.
9.3C = Harmful to terrestrial vertebrates.

Persistence and degradability	No data available
Bioaccumulation	No data available
Mobility in Soil	No data available
Other adverse effects	No data available

Do not allow to enter waterways.

Section 13. Disposal Considerations

Disposal Method: Place recovered product into an appropriate waste container for disposal through appropriate waste company or specialized landfill in accordance with local regulations. Ensure container is sealed and isolated away from ignition sources.

Precautions: Ensure waste container containing recovered product is labelled "Hazardous Waste – Flammable, Ecotoxic". If triple rinsing container, add rinsate to waste container for disposal.

Disposal methods to avoid: Do not allow to enter waterways.

Section 14 Transport Information

This product is classified as a Dangerous Good for transport in NZ ; NZS 5433:2012 and Australian Dangerous Goods Code ADG7 and NOHSC:1008(2004)

Road and Rail Transport

UN No: 1263
 Class-primary 3
 Packing Group III
 Proper Shipping Name: PAINT

Air Transport

UN No: 1263
 Class-primary 3
 Packing Group III
 Proper Shipping Name: PAINT

Marine Transport

UN No: 1263
 Class-primary 3
 Packing Group III
 Proper Shipping Name: PAINT

Section 15 Regulatory Information

**This substance is hazardous according to:
 New Zealand - The HSNO (Minimum Degrees of Hazard) Regulations 2001
 Australia – Approved Criteria for Classifying Hazardous Substances
 [NOHSC:1008(2004)]**

Poison Schedule: Schedule 5

New Zealand:

EPA Approval Code: Surface Coatings and Colourants (Flammable, Toxic [6.7]) – HSR002669

HSNO Classification: 3.1C, 6.1E(asp), 6.3A, 6.5B, 6.7B, 6.8B, 6.9B, 8.3A, 9.1D, 9.3C

HSNO Controls:

Trigger quantities for this substance:

	Trigger Quantity
Approved Handler	Not required
Location Certificate	500L (>5L), 1500L(<5L), 250L open
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	1000L
Emergency Response Plan	10000L
Stationery containment	10000L
Restriction of Use	None

Section 16 Other Information**Glossary**

EC50 Median effective concentration.
 EEL Environmental Exposure Limit.
 EPA Environmental Protection Authority
 HSNO Hazardous Substances and New Organisms.
 LC50 Lethal concentration that will kill 50% of the test organisms inhaling or ingesting it.
 LD50 Lethal dose to kill 50% of test animals/organisms.
 LEL Lower explosive level.
 OSHA American Occupational Safety and Health Administration.

TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit

1. HSNO Approved Code of Practice: Preparation of Safety Data Sheets, September 2006.
2. Australia – Approved Criteria for Classifying Hazardous Substances -[NOHSC:1008(2004)]
3. Safework Australia: Preparation of SDS sheets for hazardous chemicals (Code of Practice).

Disclaimer

This document has been issued by TCC (NZ) Ltd and serves as their Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the Australian manufacturer, if further information is required.

Issue Date: 7 November 2016 Review Date: 7 November 2021