

PRODUCT DATA SHEET

NORGLASS LABORATORIES PTY.LTD.
A.B.N. 92 001 807 245
P.O. Box 312, Neutral Bay. NSW 2089 Australia
59 Moxon Road, Punchbowl NSW
Ph: 61 2 9708 2200 Fax: 61 2 9796 3069
Email: norglass@bigpond.net.au
www.norglass.com.au



WEATHERFAST PRI-COAT

DESCRIPTION: A heavy-bodied off-white general purpose primer and combined undercoat with fast drying and the easiest of sanding properties.

USES: The superfine texture of Weatherfast PRI-COAT makes this the ideal preparation coating for timbers and many other surfaces. PRI-COAT is low in odour when used in confined spaces and is fast drying.

PROPERTIES (at 25°C)

COLOUR:	Off white
TOXICITY:	See Precautions
FINISH:	Flat
COVERAGE:	This product will cover up to 12 sq. metres per litre per coat. Less on more absorbent surfaces.
DRYING TIME:	Touch dry in 30 minutes at 20°C.
RECOATING:	After 16 hours. Allow longer time for colder conditions, or multiple wet on wet applications.
POT LIFE:	N/A
MIXING RATIO:	N/A
SPRAYING:	Wet on wet coats can be applied using up to 33 $\frac{1}{3}$ Weatherfast Spraying Thinners. Adjust the thinning ratio according to the pressure and type of equipment being used.
THINNING:	Not recommended for brush or roller use. Spraying – Thin with up to 33 $\frac{1}{3}$ % of Weatherfast Spraying Thinners.
WEIGHT/LITRE:	1.465
VOLUME SOLIDS:	75%

FLASH POINT:	32°C
CLEAN UP:	WEATHERFAST BRUSHING OR SPRAYING THINNERS
U.N. NUMBER:	1263
PREPARATION:	New Timber – Sand and remove dust from the grain with clean cloths soaked in NORCLEAN-PLUS and allow to dry. Other substrates – Refer to appropriate NORGLASS INFORMATION GUIDES for advice.
APPLICATION:	Stir contents before use. Ensure that the surface is dry and free from contaminants. Apply by brush and short nap roller and allow 24 hours to dry. If spraying, wet on wet coats are possible but longer drying time may be required for all the solvent evaporation to take place before over coating.
TRANSPORTATION:	Dangerous goods, Class 3.2 Flammable liquid Hazchem 3[Y] P.G. III SIZES: 4litre, 2litre, 1litre, 500ml and 250ml
PRECAUTIONS:	Provide adequate ventilation during use and do not smoke. Wear correct apparatus when spraying. Do not use on areas of continuous immersion. Do not use under 2 pack paints.
FIRST AID:	If poisoning occurs call a doctor or Poisons Information Centre (Aust) on 13 11 26 or (NZ) 0800 764 766 and have label information ready. If swallowed DO NOT induce vomiting. Give large quantities of water or milk. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and consult a doctor. Remove contact lenses if present and easy to do and continue rinsing. If skin contact causes irritation, remove contaminated clothing and wash skin thoroughly. If breathing difficulty arises remove to fresh air. Apply artificial respiration if not breathing.
SPECIAL INSTRUCTIONS:	Can disposal – Allow paint residues to harden in the can and then crush and consign to landfill.