

PRODUCT DATA SHEET



NORGLASS LABORATORIES PTY.LTD.
A.B.N. 92 001 807 245
P.O. Box 312, Neutral Bay. NSW 2089 Austr
59 Moxon Road, Punchbowl NSW
Ph: 61 2 9708 2200 Fax: 61 2 9796 3069
Email: norglass@bigpond.net.au
www.norglass.com.au

WEATHERFAST PREMIUM TIMBER OIL

DESCRIPTION: A modified, low odour resin coating for timber where a natural grain appearance is desired. Contains U/V inhibitors for added protection. Fast drying and non-greasy film.

USES: Primary use is for open grained timbers/decks where a temporary “natural” wet look is desired without the cumulative effect of build-up coats being produced which would involve eventual stripping.

PROPERTIES (at 20°C)

COLOUR:	Light amber
TOXICITY:	N/A
FINISH:	Satin
COVERAGE:	9-12sq. metres per litre per coat (subject to timber porosity)
DRYING TIME:	Touch dry: 1 hour at 20 degrees C and 50% relative humidity
RECOATING:	Multiple coats can be used providing that they are all applied in a wet on wet fashion . Once drying commences further coats will only be deposited on top of the previous layer and thus produce a “varnish like” film. Where this happens, eventual stripping will be required to reinstate the original condition.
POT LIFE:	N/A
MIXING RATIO:	N/A
THINNING:	Not recommended
WEIGHT/LITRE:	840g/litre
VOLUME SOLIDS:	24%
FLASH POINT:	37°C

- CLEAN UP:** Weatherfast Brushing Thinners
- U.N. NUMBER:** 1263
- PREPARATION:** **TEAK:** Sand down/caustic scrub the surface until all traces of oxidised material are removed. When the natural honey coloured timber is produced a liberal wash down with Acetone or Methylated Spirits on clean rags is recommended to (a) remove the sanding dust and (b) to produce a dry, oil-free, porous state of timber that will **increase** the penetration of the **Norglass Premium Timber Oil**.
- OTHER TIMBERS:** Treat the same as above. On more dense wood the penetration of **Norglass Premium Timber Oil** will obviously be restricted therefore the **less** number of coats can be applied. When the surface starts to produce a “varnished-like” finish, cease applying more product (unless used internally and screened from direct U/V) as this will only involve more work as the coating structure degrades.
- APPLICATION:** Use a brush, roller or pad method. Apply liberally to a square metre or two and repeat again and again as absorption becomes apparent. Move on in this fashion until the surface is adequately coated. Alternatively, apply one liberal coat over an area that takes no more than 20 minutes to cover and then repeat the process again (and again if required).
Allow a minimum of 4 hours to dry before light foot traffic. Overnight drying for normal use.
- TRANSPORTATION:** Flammable liquid. Dangerous Goods Class 3.2.
Sizes available - 20litre, 4litre, 1litre, 500ml.
- PRECAUTIONS:** Provide adequate ventilation during use.
Keep away from naked flame and do not smoke.
Do not use in damp conditions or below 10 C.
- FIRST AID:** If poisoning occurs call a doctor or Poisons Information Centre (Aust) on 13 11 26 or (NZ) 0800 764 766 and have label information ready.
If swallowed DO NOT induce vomiting. Give large quantities of water or milk. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and consult a doctor. Remove contact lenses if present and easy to do and continue rinsing. If skin contact causes irritation, remove contaminated clothing and wash skin thoroughly. If breathing difficulty arises remove to fresh air. Apply artificial respiration if not breathing.
- SPECIAL INSTRUCTIONS:**